

NRAG7.E236456

Programmable Controllers for Use in Hazardous Locations Certified for Canada

[See UL Online Certification Directory](#)

[See General Information for Programmable Controllers for Use in Hazardous Locations Certified for Canada](#)

UNITRONICS (1989) (R'G) LTD

UNITRONICS BLDG
PO BOX 300, AIRPORT CITY
70100 BEN-GURION AIRPORT, ISRAEL

Class I, Division 2, Groups A, B, C and D.

Communication modules, Models: UAC-CX-01RS4, V200-19-R4, V200-19-RS4, V200-19-RS4-X, V200-19-ET1, V100-17-RS4X, V100-17-RS4, V100-17-ET2, V100-17-CAN, V200-19-ET2.

Graphic operator panels, Models: V120-22-UN2, V120-22-UA2, V120-22-T1, V120-22-T2C, V350-35-R34, V130-33-R34, V130-T4-ZK1, V430-J-R34, SM43-J-T20, SM35-J-T20, V230-13-B20B, V260-16-B20B, V280-18-B20B, V570-57-T20B, V570-57-T20B-J, V1210-T20B, V1210-T20BJ, V1040-T20B, V700-T20BJ, V350-J-RA22, V350-35-RA22.

Input/Output expansion modules, Models: UID-W1616R, UIA-0800NH, UID-0808R, UIA-0006, IO-DI8-TO8, IO-DI8-TO8-L, IO-TO16, IO-DI16, IO-DI16-L, IO-RO16, IO-RO16-L, IO-AI4-AO2, IO-AO6X, IO-ATC8.

Isolated universal converters, Models: M90-19-R4.

Programmable controllers, Models: US7-B10-B1, US5-B10-B1, US7-B5-B1, US5-B5-B1, USP-104-B10, M90-T, M90-TA2-CAN.

Models M91-2-T2C, M91-2-UN2, M91-2-T1, M91-2-UA2, M91-2-R6, M91-2-R6C, M91-2-R1, M91-2-R2C, US10-B10-TA32, US10-B5-TA32, US10-C10-TA32, US10-C5-TA32, US5-B10-TA32, US5-B5-TA32, US5-C10-TA32, US5-C5-TA32, US7-B10-TA32, US7-B5-TA32, US7-C10-TA32, US7-C5-TA32, USC-B5-TA32, USC-C10-TA32, USC-C5-TA32, USC-B10-TA32, US7-T5-ZK1.

Programmable controllers (TYPE 4X), Models: US7-T10-B1, US7-T5-B1, US5-T10-B1, US5-T5-B1, M91-T4-R1, M91-T4-R2C, M91-T4-R6, M91-T4-R6C, M91-T4-T1, M91-T4-T2C, M91-T4-UA2, M91-T4-UN2, V130-T4-R34, V130-T4-ZK1, V130-J4-R34.



Snap-in I/O modules, Models: V200-18-E6B, V200-18-E6BL.

Expansion adapter, Models: UAG-CX-XKPxxx, UAG-XKPxxx, EX-A2X.

CPU Module for Touch Screen Display Panels, Model: USC-P-B10.

NOTE - All the models mentioned above may be followed by an alphanumeric suffix. This suffix is for customer designation and may also designate that the models are installed with UL-Listed communication modules and or UL-Listed snap-on I/O modules.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

The listed programmable controllers named may be modify by "-J" in the middle. The modifier -J, which signifies a cosmetic difference (the front panel is flat), replaces the numerals 11/33/35/57 if they appear in the controllers name.

For example, controller models named JZ10-11-R10, V130-33-T38, V350-35-T38, V570-57-T20B, V1040-T20B & JZ20-R16, will be modified to JZ10-J-R10, V130-J-T38, V350-J-T38, V570-J-T20B, V1040-J-T20B & JZ20-J-R16, respectively.

Reprinted from the Online Certifications Directory with permission from UL